

SPECIFICATIONS

4308 V-RAKE

MODEL..... 4308 Wheel Rake

DIMENSIONS AND WEIGHTS

Length (Overall) IN (mm)..... 156 (3962)
Width (Transport) IN (mm) 114 (2896)
Weight LB (kg)..... 1125 (510)

MAINFRAME

Raking Positions.....3
Raking Widths FT (m) Three Positions from 16 to 20 (4.88 to 6.10)
Windrow Widths IN (mm) Variable from 48 to 72 (1219 to 1829)
Frame Fold Hydraulic
TiresST175/80D13
Wheel Track Width (Center to Center) IN (mm) 41.5" (1054)

FINGER WHEELS

Number8
Overall Diameter In (mm) 55 (1397)
Number of Rake Tines per Wheel40
Rake Tine Diameter IN (mm) 0.3 (7)
Rake Wheel Bearings..... Tapered Roller Bearings w/Dust Covers
Wing Flex Limited
Number of Rake Wheels per Arm.....2

TRACTOR REQUIREMENTS

Horsepower 25 hp (19 kW)
Hydraulics..... One Single Acting Remote Valve (Hydraulic Fold)

STANDARD EQUIPMENT

Screw Type Tongue Jack

OPTIONAL KITS (Field Installed)

None

(Specifications and design are subject to change without notice and without liability therefore.)

SPECIFICATIONS

4310 V-RAKE

MODEL..... 4310 Wheel Rake

DIMENSIONS AND WEIGHTS

Length (Overall) IN (mm)..... 186 (4724)
Width (Transport) IN (mm) 114 (2896)
Weight LB (kg)..... 1275 (578)

MAINFRAME

Raking Positions.....3
Raking Widths FT (m) Three Positions from 18 to 22 (5.49 to 6.71)
Windrow Widths IN (mm) Variable from 48 to 72 (1219 to 1829)
Frame FoldHydraulic
TiresST175/80D13
Wheel Track Width (Center to Center) IN (mm) 56" (1422)

FINGER WHEELS

Number10
Overall Diameter In (mm) 55 (1397)
Number of Rake Tines per Wheel40
Rake Tine Diameter IN (mm) 0.3 (7)
Rake Wheel Bearings.....Tapered Roller Bearings w/Dust Covers
Wing Flex Limited
Number of Rake Wheels per Arm.....2

TRACTOR REQUIREMENTS

Horsepower 25 hp (19 kW)
Hydraulics..... One Single Acting Remote Valve (Hydraulic Fold)

STANDARD EQUIPMENT

Screw Type Tongue Jack

OPTIONAL KITS (Field Installed)

Center Kicker Wheel

(Specifications and design are subject to change without notice and without liability therefore.)

SPECIFICATIONS

4312 V-RAKE

MODEL..... 4312 Wheel Rake

DIMENSIONS AND WEIGHTS

Length (Overall) IN (mm)..... 216 (5486)
Width (Transport) IN (mm) 126 (3200)
Weight LB (kg)..... 1440 (653)

MAINFRAME

Raking Positions.....3
Raking Widths FT (m) Three Positions from 20 to 24 (6.10 to 7.32)
Windrow Widths IN (mm) Variable from 48 to 72 (1219 to 1829)
Frame Fold.....Hydraulic
TiresST175/80D13
Wheel Track Width (Center to Center) IN (mm)Adjustable up to 68.5" (1740)

FINGER WHEELS

Number 12
Overall Diameter In (mm) 55 (1397)
Number of Rake Tines per Wheel 40
Rake Tine Diameter IN (mm) 0.3 (7)
Rake Wheel Bearings.....Tapered Roller Bearings w/Dust Covers
Wing Flex Limited
Number of Rake Wheels per Arm.....2

TRACTOR REQUIREMENTS

Horsepower 30 hp (22 kW)
Hydraulics..... One Single Acting Remote Valve (Hydraulic Fold)

STANDARD EQUIPMENT

Screw Type Tongue Jack

OPTIONAL KITS (Field Installed)

Center Kicker Wheel

(Specifications and design are subject to change without notice and without liability therefore.)